## ASSIGNED

## AMENDED PERMIT

Nº 41867

## APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

Date	e of filing in State Engineer's Office	JUL 2 3 1980	
Corı	rected application filed		
Мар	filed		
	<del>-</del>		
_		nt	
Р.	Strect and No. or P.O. Box No.	, of Hawthorne City or Town	
Ne	evada 89415	nereby make application for permission to appropriate the public	
wate		d. (If applicant is a corporation, give date and place of incorpora-	
tion	; if a copartnership or association, give names of	of members.)	
*			
1.	The source of the proposed appropriation is	an underground source Name of stream, lake, spring, underground or other source	
2.	The amount of water applied for is	O. 5 One second-foot equals 448.83 gals, per min.	
		One second-foot equals 448.83 gals, per min.	
_	•		
3.		wer, mining, manufacturing, domestic, or other use. Must limit to one use.	
4.	If use is for:		
	(a) Irrigation, state number of acres to be irrigated:		
	(b) Stockwater, state number and kinds of an	nimals to be watered:	
	(c) Other use (describe fully under "No. 12. Remarks"		
	(d) Power:		
	•		
	•		
5.		the following point: in the S.W. 1 of the N.E. 1 of Section  Describe as being within a 40-acre subdivision of public	
	survey, and by course and distance to a section corner. If	eral County, Nevada., from which the northwest on unsurveyed land, it should be so stated.	
	corner of said Section 8 bears N	. 72°47'17" W. a distance of 3852.53 feet.	
6.	Place of use. N.E. 4 (158.59 Ac.), N.W. 4 (142.33 Ac.), and S.W. 4 (152.98 Ac.), all of  Describe by legal subdivision. If on unsurveyed land, it should be so stated.		
	Section 8, T.7N., R.30E., M.D.B.&M., Mineral County, Nevada.		
	,		
7.	Use will begin about January. ]	and end about December 31, of each year.  Month and Day	
		provisions of NRS 535.010 you may be required to submit plans and	
	specifications of your diversion or storage wo	orks.) Pump and pipe system to serve parcels State manner in which water is to be diverted, i.e. diversion structure, ditches and	
	as developed.		
9.			

	Estimated time required to construct work	If well completed, desc	ribe works.	
11.	Estimated time required to complete the approximated time required to complete the approximation and the second se	pplication of water to beneficial use	_	
12.	Remarks: For use other than irrigation or stock watering, state number and type of units to be served or annual consumptive use.			
	•	er is for a Quasi Municipal w	water system to serve	
	approxi <u>amate</u> ly 50 reside	ences with domestic water and	yard irrigation.	
Com:	pared bc/bl bc/bl	By s/Robert L. Ful P.O. Box 517 Carson City, Ne	ler (agent)	
Prote	sted			
	APPRO	OVAI		
		OVAL OF STATE ENGINEER		
	This is to certify that I have examined the wing limitations and conditions:	ne foregoing application, and do hereby	grant the same, subject to the	
'eas	conable lowering of the static	water level. This well shal	l he couinned with a	
wo lust nst lccu	(2) inch opening for measuring be installed and maintained talled and maintained in the distance measurements must be keptalizing meter must be installed of Completion of Work is fil	y depth to water. If the well to prevent waste. A totalizing ischarge pipeline near the po to of water placed to beneficing I before any use of water beg	l is flowing, a valve ng meter must be int of diversion and al use. The	
two nust inst accu tota Proo	be installed and maintained talled and maintained in the di alled and maintained in the di crate measurements must be kept alizing meter must be installed	g depth to water. If the well to prevent waste. A totalizing ischarge pipeline near the po to of water placed to beneficing is before any use of water beg ed.	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the	
The	be installed and maintained talled and maintained in the di alled and maintained in the di rate measurements must be kept dizing meter must be installed of Completion of Work is fil	depth to water. If the well to prevent waste. A totalizing ischarge pipeline near the post of water placed to beneficing before any use of water begarded.	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  capplied to beneficial use, and	
iwo nust nst ccu ota roo	be installed and maintained to alled and maintained in the distrate measurements must be kept alizing meter must be installed of Completion of Work is fill amount of water to be appropriated shall be exceed	depth to water. If the well to prevent waste. A totalizing ischarge pipeline near the post of water placed to beneficing before any use of water begarded.	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  capplied to beneficial use, and t not to exceed	
wo nust nst ccu ota roo	be installed and maintained to alled and maintained in the distrate measurements must be kept alizing meter must be installed of Completion of Work is fill amount of water to be appropriated shall be exceed	depth to water. If the well to prevent waste. A totalizing ischarge pipeline near the post of water placed to beneficing before any use of water begard.  be limited to the amount which can be considered to the amount which can be considered.	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  e applied to beneficial use, and t not to exceed	
wo nust nst accument of the accument to the ac	be installed and maintained to alled and maintained in the distrate measurements must be kept alizing meter must be installed of of Completion of Work is fill amount of water to be appropriated shall be exceed.  0.5  3.25 million gallons annually.	depth to water. If the well to prevent waste. A totalizing scharge pipeline near the post of water placed to beneficing before any use of water beginned.  be limited to the amount which can be completed on or before	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  applied to beneficial use, and t not to exceed  August 20, 1982	
wo nust nst ccu ota roo	be installed and maintained to alled and maintained in the distrate measurements must be kepturate measurements be installed of of Completion of Work is fill amount of water to be appropriated shall be exceed	depth to water. If the well or prevent waste. A totalizing scharge pipeline near the post of water placed to beneficing before any use of water beginned.  be limited to the amount which can be completed on or before	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  applied to beneficial use, and t not to exceed  August 20, 1982  September 20, 1982	
wo nustine in the action of the action of the Application of the Appli	be installed and maintained to alled and maintained in the distrate measurements must be kept alizing meter must be installed of of Completion of Work is fill amount of water to be appropriated shall be exceed.  0.5  2.25 million gallons annually.  The must be prosecuted with reasonable diligitation of work shall be filed before ication of water to beneficial use shall be reserved.	depth to water. If the well to prevent waste. A totalizing ischarge pipeline near the post of water placed to beneficial before any use of water begins ed.  be limited to the amount which can be completed on or before	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  applied to beneficial use, and t not to exceed  August 20, 1982  September 20, 1982  August 20, 1987	
CWO DUST INST ICCU COTA Proof Appl Proof	be installed and maintained to alled and maintained in the distrate measurements must be kepturate measurements be installed of of Completion of Work is fill amount of water to be appropriated shall be exceed	be limited to the amount which can be completed on or before and be completed on or before use shall be filed on or before	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  applied to beneficial use, and t not to exceed  August 20, 1982  September 20, 1982  August 20, 1987  September 20, 1987	
two nustinst inst accu tota Proof  18 Work Proof Appl Proof	be installed and maintained to alled and maintained in the distrate measurements must be kept alizing meter must be installed of of Completion of Work is fill amount of water to be appropriated shall be exceed	be limited to the amount which can be completed on or before and be completed on or before and be filed on or before	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  e applied to beneficial use, and t not to exceed  August 20, 1982  September 20, 1982  August 20, 1987  September 20, 1987	
two nust inst inst inst inst inst inst inst in	be installed and maintained to alled and maintained in the distrate measurements must be kept alizing meter must be installed of of Completion of Work is fill amount of water to be appropriated shall be exceed	be limited to the amount which can be completed on or before	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  e applied to beneficial use, and t not to exceed  August 20, 1982  September 20, 1982  August 20, 1987  September 20, 1987  September 20, 1987  September 20, 1987	
two nust inst inst accu tota accu tota roo  The a not to  Mork Proof Appl Proof Map Comp	be installed and maintained to alled and maintained in the distrate measurements must be kept alizing meter must be installed of of Completion of Work is fill amount of water to be appropriated shall be exceed.  0.5  2.25 million gallons annually.  The must be prosecuted with reasonable diliging a must be prosecuted with reasonable diliging for completion of work shall be filed before ication of water to beneficial use shall be referred in support of proof of beneficial use shall be shall be support of proof of beneficial use shall be shall be support of proof of beneficial use shall be shall be support of proof of beneficial use shall be support of proof of beneficial use shall better to be shall be support of proof of beneficial use shall better to be shall be support of proof of beneficial use shall better to be shall be support of proof of beneficial use shall be support of proof of beneficial use shall be support of work filed.  OCT 21.1983	depth to water. If the well to prevent waste. A totalizing the post of water placed to beneficing the before any use of water begard.  be limited to the amount which can be completed on or before	l is flowing, a valve ng meter must be int of diversion and al use. The ins or before the  e applied to beneficial use, and t not to exceed  August 20, 1982  September 20, 1982  August 20, 1987  September 20, 1987  September 20, 1987  September 20, 1987	